New 15 Digit Furnace Model Nomenclature

	Brand	Configuration	Feature - Efficiency	Heating Stages	Cabinet Width	Capacity	Capacity	Capacity	Major Modification	0 Voltage	Airflow-Blower Type	Airflow-Blower Type	Draft Inducer Speed	Hinor Modification	Service Digit
Digit	1	2	3	± 4		6	7	8	9	>	₹ 11		<u>=</u>	∑	<u>3</u>
Digit													13		
Furnaces	T	U	D	1	В	0	8	0	Α	9	Н	3	1	Α	Α
Upflow/Horizontal	T	U													
Downflow/Horizontal	T	D													
80% Standard Induced Draft			Е												
80% Premium Induced Draft			D												
90% Condensing			С												
90% Condensing Direct Vent			Χ												
Single Stage				1											
Two Stage				2											
Three Stage				3											
14.5" Cabinet Width					Α										
17.5" Cabinet Width					В										
21.0" Cabinet Width					С										
24.5" Cabinet Width					D										
Heating Input MBTUH						0	8	0							
Major Design Change									Α						
115 Volts / Natural Gas										9					
115 Volts / Natural Gas with Integrated Electronic Filter										F					
3 Ton Standard PSC Motor (36 = 3 tons)											3	6			
3 Ton High Efficiency Motor (H3 = 3 ton)											Н	3			
3 Ton Variable Speed Motor (V3 = 3 ton)											٧	3			
Single Speed													1		
Two Speed													2		
Variable Speed													٧		
Minor Design Change														Α	
Service Digit															Α